

EMS Multi-Track (Non-section 12) Aluminium Grid Entrance Matting

TYPICAL SPECIFICATION

N10 General Fixtures/Furnishings/Equipment **300** Entrance Matting **40** Miscellaneous Fittings

Reference	EMS Multi-Track (Non section 12)
Height	13mm or 17mm
Insert	Multi-directional rubber infill
Installation	Recessed in matwell. Can be used in conjunction with drainage grating systems

DETAILED SPECIFICATION

Reference	EMS Multi-Track (NS12)
Conformity	Manufactured to ISO9001:2008. Conforms to current BS8300 DDA Regulations
Grid Construction	Aluminium – minimum 80% recycled content in closed construction format with drainage holes as standard
Insert	Multi-directional rubber infill. Colour Black
Height	13mm or 17mm
Module Size	EMS panels are manufactured specifically to customer requirements. Panel lengths upto 4600mm left to right as required
Fire Rating	Hot Nut metal test
Installation	Recessed in matwell or surface-laid with ramp frame.
Anodising Options	Aluminium grid can be anodised black, gold or bronze

Description

EMS Multi-Track (NS12) is a primary matting system for specification in heavy duty transport applications where removal of footborne dirt is essential. EMS products are manufactured for high traffic areas such as hotels, retail stores, shopping centres, schools, hospitals and airports to name a few.

The matting is bespoke made. Each front to back panel has a male and female edge which lock together. Any left to right size can be achieved by simply butting the panels together. No T-Bar is required. All EMS matting systems come with a 10 year guarantee and interchangeable infills.

Entrance Matting Systems

Unit 12 -14 Freiston Enterprise Park, Boston, Lincolnshire PE22 0JZ

**T: +44 (0) 1205 761776 F: +44 (0) 1205 761811 E: info@entrance-matting.com
W: www.entrance-matting.com**