

EMS TDR (Entrance Matting Systems Tretford Design Range) Aluminium Grid Entrance Matting

TYPICAL SPECIFICATION

N10 General Fixtures/Furnishings/Equipment

300 Entrance Matting

40 Miscellaneous Fittings

Reference	EMS Tretford Design Range (TDR)	
Height	12mm	
Insert	Natural goat hair infills available in 60 Tretford colours	
	512 Dapple Grey 513 Sage 514 Bilberry 515 Siver 616 BrillantBlue 517 Sky 520 Damson 523 Larch 524 Russet 527 DriedLavender	
	528 Apple 530 Heather 532 Sisal 534 Arthracte 538 Silver Birch 542 Night-Sky 555 Wild-Rice 558 Peacock 559 Burnt Orange 562 Rose-Sunset	
	565 Ever-Green 566 Lichen 557 Lagoon-Blue 568 Jonquile 559 Clover 571 Mushroom 572 Milk/Chocolate 574 Autumn Fern 575/CCRNFLOWER 576 Aquamarine	
	577 Burgundy 579 Petrol-Green 580 Lettuce-Leaf 581 Deep-Purple 584 Black-Berry 585 Orange-Squash 587 Double-Cream 589 Amethyst 590 Coffee-Bean 592 Lovely-Lilac	
	593 Diplomat-Red 601 Truffle 614 Agean 615 FreshWater 616 Chill 617 Magenta 618 Indigo 619 Aubergine 620 Charcoal 622 Taupe	
	623 Saddle 624 DarkChocolate 625 Denim 628 Blue 631 Lipstick 632 Black 643 Meion 646 AntiqueRose 697 Lime 699 Olive-Tang	
Installation	Recessed in matwell or surface-laid with ramp frame	

DETAILED SPECIFICATION

Reference	EMS Tretford Design Range (TDR)
Conformity	Manufactured to ISO9001:2008. Conforms to current BS8300 DDA Regulations Flammability: BS4790: 1987: Mean Radius of burning – 25mm. Class – Low. IBM and ICL Electrical Resistance: Tested at 40% RH and 20°C – Passed.
Grid Construction	Aluminium – Minimum 95% recycled content in closed construction format
Insert	Natural goat hair infills available in 60 Tretford colours
Height	12mm
Module Size	EMS panels are manufactured specifically to customer requirements. Panel lengths available up to 4000mm left to right as required (Anodised panel lengths vary – see below)
Installation	Recessed in matwell or surface-laid with ramp frame. Suitable for use with underfloor heating.
Anodising Options	Aluminium grid system and framework to suit can be anodised in colours: Black – Available in 4000mm module length Light Gold – Available in 2600mm module length Medium Gold - Available in 2600mm module length Dark Gold - Available in 2600mm module length Gun Metal Grey – 2500mm Maximum Panel length Light Bronze - 1600mm Maximum Panel length Medium Bronze – 4000mm Maximum Panel length Dark Bronze – 4000mm Maximum Panel Length
Light Fastness	BS 1006: 1990 5-6 very slight to none
Water Fastness	BS 1006: 1990 4 very slight
Rubbing Fastness	BS 1006: 1990 4 very slight
Accreditations	Global Green Tag Certified - GreenRate Level A

Description

EMS Tretford Design Range aluminium grid entrance matting is a primary matting system for specification in commercial applications where the removal of footborne dirt is essential. EMS products are manufactured for high traffic areas such as residential and care homes, medical practice, offices and administrative buildings, family homes, hotels, retail sectors, shopping centres, schools, hospitals and airports to name a few.

The matting is bespoke made. Each front to back panel has a male and female edge which interlock together. Any left to right size can be achieved by simply butting the panels together. No T-Bar is required.

All EMS matting systems come with a 15 year guarantee and interchangable infills. Full details of conditions and limits of guarantees are available upon request.

Entrance Matting Systems
Unit 12 -14 Freiston Enterprise Park, Boston, Lincolnshire PE22 0JZ

T: +44 (0) 1205 761757 F: +44 (0) 1205 761811 E: info@entrance-matting.com

W: www.entrance-matting.com