

**EMS DC009** (Entrance Matting Systems Debris Channel with 009 inserts) Aluminium Grid Entrance Matting

## **TYPICAL SPECIFICATION**

**N10** General Fixtures/Furnishings/Equipment      **300** Entrance Matting      **40** Miscellaneous Fittings

Reference	EMS DC009
Height	12mm
Insert	Nylon brush black mix
Installation	Recessed in matwell or surface-laid with ramp frame

## **DETAILED SPECIFICATION**

Reference	EMS DC009
Conformity	Manufactured to ISO9001:2008. Conforms to current BS8300 DDA Regulations
Grid Construction	Aluminium – minimum 80% recycled content in closed construction format
Insert	Solution dyed Nylon brush - black, Dark Grey, Light Grey, Silver, Beige, Blue, Red mix
Height	12mm
Module Size	EMS panels are manufactured specifically to customer requirements. Panel lengths upto 4000mm left to right as required
Fire Rating	Hot Metal Nut BS4790:1987 (1996)
Installation	Recessed in matwell or surface-laid with ramp frame
Anodising Options	Aluminium grid can be anodised black, gold or bronze

## **Description**

EMS Debris Channel aluminium grid entrance matting is a primary matting system for specification in commercial applications where the removal of footborne dirt is essential. EMS products are manufactured for high traffic areas such as hotels, retail stores, shopping centres, schools, hospitals and airports to name a few.

The matting is bespoke made. Each front to back panel has a male and female edge which lock together. Any left to right size can be achieved by simply butting the panels together. No T-Bar is required. All EMS matting systems come with a 10 year guarantee and interchangeable infills.

### **Entrance Matting Systems**

**Unit 12 -14 Freiston Enterprise Park, Boston, Lincolnshire PE22 0JZ**

**T: +44 (0) 1205 761776      F: +44 (0) 1205 761811      E: [info@entrance-matting.com](mailto:info@entrance-matting.com)  
W: [www.entrance-matting.com](http://www.entrance-matting.com)**