

EMS Multi-Track Natural (Low smoke & Toxic fume emmission multi-directional infill) Aluminium Grid Entrance Matting

TYPICAL SPECIFICATION

N10 General Fixtures/Furnishings/Equipment

300 Entrance Matting

40 Miscellaneous Fittings

| Reference | EMS Multi-Track Natural |
|--------------|---|
| Height | 13mm or 17mm |
| Insert | Multi-directional Low Smoke & Toxic fume emmission rubber infill |
| Installation | Recessed in matwell. Can be used in conjunction with drainage grating systems |

DETAILED SPECIFICATION

| Reference | EMS Multi-Track Natural |
|-------------------|--|
| Conformity | Manufactured to ISO9001:2008. Conforms to current BS8300 DDA Regulations |
| Grid Construction | Aluminium – minimum 80% recycled content in closed construction format with drainage holes as standard |
| Insert | Multi-directional Low Smoke & Toxic fume emmission rubber infill. Colour Black |
| Height | 13mm or 17mm |
| Module Size | EMS panels are manufactured specifically to customer requirements. Panel lengths upto 4600mm left to right as required |
| Fire Rating | BS EN ISO 9239-1:2010 |
| Installation | Recessed in matwell or surface-laid with ramp frame. |
| Anodising Options | Aluminium grid can be anodised black, gold or bronze |

Description

EMS Multi-Track Natural is a primary matting system for specification in heavy duty transport applications where removal of footborne dirt is essential. It complies with LUL Section 12 fire rating approval. EMS products are manufactured for high traffic areas such as hotels, retail stores, shopping centres, schools, hospitals and airports to name a few.

The matting is bespoke made. Each front to back panel has a male and female edge which lock together. Any left to right size can be achieved by simply butting the panels together. No T-Bar is required. All EMS matting systems come with a 10 year guarantee and interchangable infills.

Entrance Matting Systems

Unit 12 -14 Freiston Enterprise Park, Boston, Lincolnshire PE22 0JZ